## (19) World Intellectual Property Organization International Bureau



## 

(43) International Publication Date 8 July 2004 (08.07.2004)

English

## (10) International Publication Number WO 2004/057684 A1

- (51) International Patent Classification7: H01L 45/00.
- (21) International Application Number:
- PCT/IB2003/005648 (22) International Filing Date: 3 December 2003 (03.12.2003)
- (25) Filing Language:
- (26) Publication Language:


(30) Priority Data:

- 02080430.8 19 December 2002 (19.12.2002) 03100583.8 7 March 2003 (07.03.2003)
- (71) Applicant (for all designated States except US): KONIN-KLLIKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): LANKHORST, Martijn, H., R. [NL/NL]; c/o Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN PIETERSON, Liesbeth [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven

- (NL). WOLTERS, Robertus, A., M. [NL/NL]; c/o Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL). MEINDERS. Erwin, R. [NL/NL]; c/o Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agent: DULJVESTIJN, Adrianus, J.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN. MW. MX. MZ. NI. NO. NZ. OM, PG, PH, PL, PT, RO, RU, SC. SD. SE. SG. SK. SL. SY. TJ. TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ELECTRIC DEVICE COMPRISING PHASE CHANGE MATERIAL



(57) Abstract: The electric device (1, 100) has a body (2, 101) with a resistor (7, 250) comprising a phase change material being changeable between a first phase and a second phase. The resistor (7, 250) has an electric resistance which depends on whether the phase change material is in the first phase or the second phase. The resistor (7, 250) is able to conduct a current for enabling a transition from the first phase to the second phase. The phase change material is a fast growth material which may be a composition of formula Sb<sub>1-c</sub>M<sub>c</sub> with c satisfying 0.05 ≤ c ≤ 0.61, and M being one or more elements selected from the group of Ge, In, Ag, Ga, Te, Zn and Sn, or a composition of formula  $Sb_aTe_bX_{100-(a+b)}$  with a, b and 100-(a+b) denoting atomic percentages satisfying  $1 \le a/b$ ≤ 8 and 4 ≤ 100-(a+b) ≤ 22, and X being one or more elements selected from Ge, In, Ag, Ga and Zn.